



NEW - L82 LED Light Units



- 3 year LED lamp warranty
- Listed for up to 75 °C operation
- CE approved universal driver
- Highest efficiency (Lumen/Watt) available in food service applications
- Colour Rendering Index >80
- Higher light output: a brighter, safer work environment
- LED strips
- 50,000-hour lamp life: reduced maintenance costs
- No ultraviolet rays: does not attract insects
- One-piece satin finish stainless steel trim
- Tempered, prismatic glass diffuser
- Recess mount installation
- Rated to IP66
- Meets DW172 requirements
- Meets requirements for NFPA 96 and N.E.C 410

Applications include:

- Commercial Kitchens
- Hospitals
- Care Homes
- Veterinary Clinics
- Railways
- Industrial Plants
- MOD
- Schools
- Mobile Kitchens

LED lights should not be installed directly above high temperature items such as chargrills and salamanders; however, our new L82 LED light suites perfectly with our existing L82 fluorescent light to allow for a combination to be fitted where required

TECHNICAL SPECIFICATION

Model No.	L821030/LED	L821040/LED
Rated Voltage Frequency	200-250V - 50/60Hz	200-250V - 50/60Hz
Protection Class	Class 1	Class 1
Power (W)	43	53
Initial Lumens	4228	4925
Kelvin	4000	4000
Lumens/Watt	98	93
Overall Trim Size	260mm x 972mm	260mm x 1276mm
Holes Required	14	14
Cut-Out Height	216mm	216mm
Cut-Out Width	927mm	1232mm



**For further information or to arrange a visit or request a demonstration
please contact our sales team on**

01327 311144 | sales@die-pat.co.uk | www.die-pat.co.uk